

ChemGrout CG-550P Air Powered Compact Grouter



Applications

- Door & window frames
- Void filling
- Slab raising
- Pavement dowel bars
- Piling encasements
- Machine base & joint grouting
- Waterproofing
- Piling encasements
- Precast tunnel joints
- Concrete floors / roofs

- Complete grouting system that provides continuous operation by combining a high efficiency paddle mixer and the field proven CG-050 2" positive displacement piston pump.
- Air or hydraulically powered, the skid mounted 550P features a 128 litre mixing tank equipped with baffles, bag breakers and a variable speed high-efficiency paddle that ensures rapid and thorough mixing.
- Once mixed, material is transferred into a 19 litre holding hopper through a slide gate specially designed to handle the most difficult materials.
- Single operation required to control both the mixer and pump, increasing productivity.
- Rugged steel framed system stands up to the toughest job site conditions.



ChemGrout CG-550P Air Powered Compact Grouter



CG-550P	Air	Hydraulic
Pump	2' Piston	2" Piston
Paddle Mixer	128 L	128 L
Output	5 gpm (19 lpm)	5 gpm (19 lpm)
Pressure	225 psi (16 bar)	400 psi (28 bar)
Weight	136 kg	186 kg
Power Required	85 cfm, 100 psi	2 supplies ea/5gpm, 1500 psi
Size	111.76 cm x 68.6 cm x 119.4 cm (L x W x H)	

