

- The compact one-person mixing pump in 230 V, alternating current, designed to spray and apply sprayed renderings, levelling compounds, dispersion paints and other materials up to 3mm in grain size.

Advantages

- PFT RITMO M can be used as a pump or a mixing pump, no matter whether you want to fill it out of buckets or bags.
- It is easy to handle, which saves time during start-up, refitting, maintenance and cleaning.
- Two water inlets permit flexible mixing intensity - and thus allow the processing of several different materials.
- Conveying and mixing performance can be set, due to the infinitely variable drive.
- Innovative arrangement of the bag opener as well as low filling height facilitate quick opening and neat emptying of the bagged material.
- The RITMO is small, light, handy, compact and on castors. Can be easily disassembled into its three modules.
- A completely equipped plastering machine: compressor, hoses, spraying gun – connect and start



Applications

- Interior plastering
- Finishing coat
- Knifing filler
- Levelling compounds
- Liquid filling compound
- Grouting mortar for door frames
- Upgraded insulation
- Dispersion paints
- Restoration mortar

Technical Data

Part No.	PFT00078401
Conveying Capacity	Max. 0.7-14 l / min
Conveying Distance	Up to 15m
Motor	230 V, 1 Ph, 50 Hz, 1.9 kW, 140-575 rpm
Hopper Content	45 litre
Rotor / Stator	B 4 – 1.5 L
Dimensions	750 x 600 x 1340 mm (L x W x H)
Filling height	900mm
Total Weight	103 kg

